

DIRECT DIMENSIONS

Spherical Laser Scanner - Model DD510

Technical Specifications

Scanner Type	Phase Shift, Hemispherical Scanner with 360° x 270° field of view
--------------	---

SYSTEM SPECIFICATIONS

Distance Measurement Method	Phase-shift
Laser Wavelength	1550 nm
Laser Type	CW
Laser Class: (IEC EN60825-1:2007)	Class 1
Scan Rate, software selectable(points/second)	208,000/ 832,000 pps
Internal Coordinate Representation Unit	0.001 mm
Angular position data	
Beam diameter at Aperture	3 mm
Internal Vertical Angular Representation Unit	1 arc sec
Internal Horizontal Angular Representation Unit	1 arc sec
Scan density control: software selectable	
Min. Vertical Point Density (points/degree)	12 ppd
Min. Horizontal Point Density (lines/degree)	2 lpd
Max Vertical Point Density (points/degree)	360 ppd
Max Horizontal Point Density (lines/degree)	78 lpd
360° Scan Time, HP mode (832,000 pps at 7200x7200 density)	1.2 min
360° Scan Time, HQ, HS modes (208,000 pps at 7200x7200 density)	4.5 min
Field-of-view (per scan, software selectable)	
Horizontal (maximum)	360°
Vertical (maximum)	270°
Physical dimensions and weight	
Weight with battery	5.8 kg
Dimensions 278mm L x 200mm H x 118mm W	

**CLASS 1
LASER PRODUCT**

STANDARD ACCESSORIES, MODEL DD510

- Built-in scan controller, allows direct scanner control and data collection without a laptop
- Wi-Fi connectivity
- Tilt sensor, dual axis
- Shipping container
- USB 2.0 cable
- AC Adapter 110/240 AC, 14-24V DC, 3.5A
- DC power cable
- Tripod Adapter
- Two Li-Ion 14V, 49Wh batteries, each provides 1 to 1.5 hours of operation
- 2-bay charger
- 1-year Limited Warranty and Basic Support contract

OPTIONAL ACCESSORIES

- Two 5MPix built-in cameras; software for automatic color data mapping is included
- SMR-compatible B&W targets and targets case
- Scanner carrying case, size approved for most domestic airlines cabin requirements, weight restrictions vary, please check with airline(s) for up-to-date regulations
- Tripod
- External hot-swappable extended battery
- Extended Warranty contract

HOST COMPUTER REQ'TS Optional, min. configuration

- Processor: 1.8 GHz or greater Pentium-compatible.
- System memory RAM 2GB or greater, 4GB recommended
- OS: Windows 7, 8 or 10; 32-bit or 64-bit editions
- USB 2.0 port

ENVIRONMENTAL

- Calibrated Operating Temperature: 5°C to 40 °C, non-condensing humidity

POWER REQUIREMENT

- 14-24V DC, 40W

Configuration (software selectable, available on all DD510 laser scanner units)	DD510_HQ ₄ 208,000 pps	DD510_HS ₄ 208,000 pps	DD510_HP ₄ 832,000 pps
Recommended Work Range (m)	0.4-70	0.4-70	0.4-70
Ambiguity Range (m)	180	360	180
Angular Uncertainty _{1,3} (arc sec)	25	25	25
Range Noise _{1,2} , mm; 90% reflectivity	0.06@0.4m-30m	0.09@0.4m-30m	0.15@0.4m-30m
Range Noise _{1,2} , mm; 10% reflectivity	0.15@0.4m-15m	0.15@0.4m-15m	0.3@1m-15m
Range Uncertainty ₃ , mm	<0.7@15m	<0.9@15m	<0.9@15m

¹ All noise and uncertainty figures are for 1 sigma level.

² Range noise -- local (short term) range variation, Lambertian surface.

³ Evaluated with contrast target best fit.

⁴ DD510_HQ, DD510_HS and DD510_HP are software selectable options, all three are available on all units.

Note: System parameters may be changed without notice; parameters are rated independently.

Direct Dimensions, Inc.

410-998-0880 ph
410-998-0887 fax

10310 S. Dolfield Road
Owings Mills, MD 21117

info@dirdim.com
www.directdimensions.com